


Tape

Product Data Bulletin



Anti-Slip



Hazard



Marking



Pipe Marking



Reflective



Vehicle

	Application	Adhesive	Material	Thickness	Shelf Life	Specification
Anti-Slip	Minimum application temperature 50°F. Surface must be clean and free from dust, dirt, oil, wax, silicone	Permanent Acrylic Pressure Sensitive	Vinyl (6 mil) 46-Grit	0.034 in	1 year stored at 70°F	ASTM-D638 PSTC-33 PSTC-7 PSTC-6 PSTC-1
Hazard	Conformable to most any surface, and will adhere to most clean dry surfaces.	Crosslinked Rubber Adhesive Pressure Sensitive	Vinyl (6 mil)	6.8 mil	1 year stored at 70°F	PPP-T-66E
Marking	Great for floor aisle marking and color-coding pipe banding applications. The coloring is throughout the vinyl so it can not scratch or scuff during wear.	Crosslinked Rubber Adhesive	Vinyl (6 mil)	6.8 mil	1 year stored at 70°F	PPP-T-66E
Pipe Marking	Minimum application temperature 10°F. Operational temperature -50°F to 120°F. Surface must be clean and free from dust, dirt, oil, wax, silicone.	Permanent Rubber	3.0 mil polyethylene 1.0 mil biaxially-oriented polypropylene lamination	3.75 mil	1 year stored at 72°F	
Reflective	Minimum application temperature 40°F. Surface must be clean and free from dust, dirt, oil, wax, silicone.	Permanent Acrylic Pressure Sensitive	Reflective	4.5-5.5 mil	1 year stored at 73°F	ASTM-D4956 DOT-C2
Vehicle Reflective	Minimum application temperature 60°F. Recommended for flat application to clean painted metal surfaces only. Not recommended for stainless steel.	Permanent Acrylic Pressure Sensitive	Vinyl Based Prismatic Reflective Film	13.0 mil	1 year stored at 73°F	NHTSA (49 CFR 571) DOT-C2